



PRODUCT SPECS



Features

Complete table assembly

1" low pressure laminate surface

Casters for easy mobility

Optional surface-attached power strip



STANDARD SPECIFICATIONS

- Single stage height range 27.5"-46.5" (top of surface)
- Raise/lower speed of 1.375" per second
- Power consumption < 0.3W

- · Ships complete, just attach base to top
- · Available in black, white or silver


OPTIONS

HANDSWITCH OPTIONS



Basic Up-Down

POWDER COAT COLOR OPTIONS



FOOT OPTIONS



T Foot

POWER STRIP OPTIONS



Power Strip No Power Strip

WORKSURFACE OPTIONS



WARRANTY INFORMATION

Two Years Worksurfaces

Three Years Electronic components such as control boxes, handswitches, motors.


Five Years Mechanical components such as crank drives, spindles.


Ten Years Structural components such as beams, feet and top supports.

TECHNICAL SPECIFICATIONS

TYPE	STROKE	HEIGHT	TRAVEL	MAX RATED	NOISE
	LENGTH	MIN / MAX	SPEED	LOAD	LEVEL
	(IN)	(IN)	(IN/sec)	(LB)	(DB)
Single Stage (SSE)	19	27.5/46.5	1.375	250	<50

STANDARD DIMENSIONS





NOTES

• Base depth: 23"

• Base height: SSE: 27.5" -46.5"

• Worksurface size: 24" x 48"

• Column dimensions: SSE: 3.35" x 2.17"

• Max load: Rated load (including table top): 250 lb.









